


CHEMICAL - DOT/TC  4 AXLES

QUALITY AND DURABILITY



SERVICE CENTERS

TREM CAR
HEAD OFFICE
790, Montrichard Avenue
St-Jean-sur-Richelieu, Québec
Canada J2X 5G4
Phone: (450) 347-7822
or (800) 363-2158
Fax: (450) 347-8372

TREM CAR
SALES & SERVICE CENTER: 
2060 Oxford Street E.
London, Ontario
Canada N5V 2Z8
Phone: (519) 452-7732
Fax : (519) 452-4861

TREM CAR.COM



Technical specifications

Code	DOT/TC 407
Working pressure	25 psi
Test pressure	45 psi
Shape	Cylindrical, cleanbore
Number of compartments	One or two compartments
Capacity	6 500 to 10 000 IG
Inner tank	T316/T316L stainless steel – 2B finish
Head	T316/T316L stainless steel – 2B finish A.S.M.E. type
Reinforcing ring	Stainless steel top hat section, fully welded
Insulation	6" fiberglass compressed to 5"
Frame	T304 stainless steel with boxed crossmembers/outriggers
Outer shell	T304 - Prebuff
End	T304 - #4 finish
Emergency valve	4" Betts chemical hydraulic valve
Outlet valve	3" Betts QRB Hydrolet
Manhole	Betts, 8310LCX, 20" – 6 lugs
Splashbox	Stainless steel with rollover protection and one 1.5" drain hose on one side
Vent	Fort Vale DOT 407 pressure / vacuum relief
Thermometer	Bulb type
Fender	Aluminum contour
Mudflap	Tremcar – white mudflaps
Ladder	One stainless steel ladder
Suspension	Intraax AA250T with Hendrickson Connex-ST self steer
Axles	Included with Hendrickson
Hubs and drums	10 stud, steel, hub pilot with cast drum
Wheel	8.25 X 22.5 steel disc, 10-holes, hub-piloted and 12.25 X 22.5
Brakes	16.5" X 7" quick change with 4S/2M Meritor ABS system
Tires	Yokohama
Nose box	Tremcar – with seven way receptacle
Fifth wheel plate	Bolted, adjustable, heavy duty plate
Landing gear	Jost, 160 000#, 2 speeds
Light and wiring	Grote wiring and lighting system
Bumper	4" X 8" stainless steel split rear end protection with underide protection
Paint	Carbon steel parts, sandblasted, primed and painted
Walkway	Aluminum Diamond Grip

Options and substitutions to standard

Distributed by